



# Premium 600

**Coating Machine** 

Premium 600

## **Premium 600:** Coating Machine

Multiple coating troughs pressing

Linear guidance and top mounted drive units

Infeed and outfeed from the front, leftside and rightside

Compatible for inline production

Touch-Screen-Display / 50 program storage locations


Stepless coating speed, freely selectable waiting periods, as well as arbitrary coating cycles are naturally

Automatic positioning of the top frame holding bar of coating car

Optional heating replace the machine a drying cabinet







## Premium 600

**Coating Machine** 

### **Options:**

- A: Warm air heating/drying unit:
  The emulsion dries completly and replaces so a external drying cabinet
- B: Multiple coatings:

  Coating at the same time up to 6 identical frames save time and money. Controlling of the clips takes place by means of foot pedals
- C: Trough edge cleaning (dry/wet):
  Automated cleaning of the trough edges by
  means of damp sponge or dry with rubber
  lip. Depending upon emulsion and trough
  length recommended
- D: Automatic draw-in/push-out: To the use in automated inline productions with frame height recognition
- E: Magazine (infeed/outfeed):
  For the automatic coating of several frames
  one behind the other without personnel
  expenditure. Output magazine also in a
  drying cabinet available
- F: Film applying unit
- G: Automatic emulsion supply

#### **Technical data:**

- Electrical connection:
   1x230V, 3x400 V (with heating),
   10A, 50/60 Hz special voltages on request
- Pneumatic connection:
   6bar
- Control:
   CPU with menu-guided touch-screen-display
- Scope of supply:
   The machine will be delivered with assembled infeed or outfeed, including a pair of troughs (length according to desire)
- Frame dimension:

Width: 4000 - 7000mm

(coating troughs maximum 6000mm)

Height: 2100 - 6500mm

ZENTNER Systems GmbH Dieselstraße16 D-32791 Lage

Fon: +49 52 32/6 99 90-0 Fax: +49 52 32/6 99 90-20 www.zentner-systems.de info@zentner-systems.de

