	and more!
	reclaiming
	washing
	developing
	coating
\wedge	



TRS - Drying Cabinet

The automatic TRS drying cabinet is ideally suited for the dry of coated screen printing stencils. Up to five screens can be dried at the same time, while the internal temperature is 40 ° C with an accuracy of 3 ° C. The incoming fresh air is cleaned through of a special filter which prevents particles on the freshly coated screens.

Max. Format (mm) TV <u>V</u> bW2SfgdW Bai W1 Ha1fSYW I [VfZ (mm) · WW2f (mm)	TRS 1100 900 x 1100 40° C ± 3 ° C 2015 W 230 V; 50 Hz 1700	TRS 1200 1200 x 1400 40° C ± 3 ° C 2015 W 230 V; 50 Hz 2000 1300	TRS 1400 1400 x 1900 40° C ± 3 ° C 2015 W 230 V; 50 Hz 2500 1300
: ŴYZf (mm)	1300	1300	1300
6WøfZ(mm) IW∦YZf(kg)	1250 200	1500 300	1700 400

Zentner Systems GmbH Dieselstraße 16 D-32791 Lage Fon: +49 52 32/6 99 90-0 Fax: +49 52 32/6 99 90-20 www.zentner-systems.de info@zentner-systems.de

